

Lens	Lens Construction (groups/elements)	Picture Angle	Minimum f/Stop	Closest Marked Focus Distance [Macro Setting] [m (ft.)]	Maximum Reproduction Ratio [Macro Setting]	Filter Attachment Size (mm)	Lens Case	Lens Hood	Dia. x Length (extension from lens mount) (mm)	Weight (g)	TC-201	TC-301	TC-14A	TC-14B	Max. number of HN-36 hoods usable	Max. number of HN-37 hoods usable
Wideangle																
15mm f/3.5 ^{*1}	11/14	110°	22	0.3 (1)	1/12.5	Provided	CL-S2, CL-17	Built-in	90 x 83.5	630	①	—	①	—	—	Not usable
18mm f/3.5 ^{*1}	10/11	100°	22	0.25 (0.85)	1/8.3	72	CL-S1, CL-34A, CL-37	HK-9	75 x 61.5	350	①	—	③	—	✓ ^{a,b} 0	✓ 0
20mm f/2.8 ^{*1}	9/12	94°	22	0.25 (0.85)	1/8.3	62	CL-S2, CL-30S	HK-14	65 x 42.5	260	①	—	①	—	✓ ^b 0	✓ 0
24mm f/2 ^{*1}	10/11	84°	22	0.3 (1)	1/8.6	52	CL-S1, CL-31S, CL-34A	HK-2	63 x 51.5	300	①	—	①	—	✓ 0	✓ 1
24mm f/2.8 ^{*1}	9/9	84°	22	0.3 (1)	1/8.8	52	CL-S1, CL-30S, CL-34A	HN-1	63 x 46	275	①	—	①	—	✓ 0	✓ 1
28mm f/2 ^{*1}	8/9	74°	22	0.25 (0.9)	1/5.4	52	CL-S1, CL-31S, CL-32S	HN-1	63 x 58.5	345	①	—	①	—	✓ 0	✓ 1
28mm f/2.8 ^{*1}	8/8	74°	22	0.2 (0.7)	1/3.9	52	CL-S1, CL-30S, CL-34A	HN-2	63 x 44.5	250	①	—	①	—	✓ 0	✓ 1
35mm f/1.4 ^{*1}	7/9	62°	16	0.3 (1)	1/5.6	52	CL-S1, CL-31S, CL-32S	HN-3	67.5 x 62	400	②	—	②	—	✓ 0	✓ 1
35mm f/2	6/8	62°	22	0.3 (1)	1/5.7	52	CL-S1, CL-31S, CL-32S	HN-3	63 x 51.5	280	①	—	①	—	✓ 0	✓ 1
45mm f/2.8 P	3/4	50°	22	0.45 (2)	1/7.6	52	Soft pouch type provided	HN-35	63 x 17	120	—	—	—	—	✓ 3	✓ 4
Normal																
50mm f/1.2	6/7	46°	16	0.5 (1.7)	1/7.9	52	CL-S1, CL-31S, CL-34A	HS-12, HR-2	68.5 x 47.5	360	①	—	①	—	✓ 1	✓ 2
50mm f/1.4	6/7	46°	16	0.45 (1.5)	1/6.8	52	CL-S1, CL-30S	HS-9, HR-1	63 x 40	250	②	—	②	—	✓ 1	✓ 3
50mm f/1.8	5/6	46°	22	0.6 (2)	1/9.6	52	CL-30S	HR-4, HS-11	63 x 27.5	145	①	—	①	—	✓ 2	✓ 3
Telephoto																
85mm f/1.4 ^{*1}	5/7	28°30'	16	0.85 (3)	1/7.9	72	CL-S2	HN-20	80.5 x 64.5	620	②	—	②	—	✓ 1	✓ 3
105mm f/1.8	5/5	23°20'	22	1 (3.5)	1/7.6	62	CL-S1, CL-15S	Built-in	78.5 x 80.5	580	②	—	②	—	✓ 1	✓ 3
105mm f/2.5	4/5	23°20'	22	1 (3.5)	1/7.7	52	CL-S1, CL-32S	Built-in	64 x 69.5	435	①	—	③	—	✓ 3	✓ 5
135mm f/2	4/6	18°	22	1.3 (4.5)	1/7.5	72	CL-S2, CL-15S	Built-in	80.5 x 93.5	860	②	—	②	—	✓ 1	✓ 4
135mm f/2.8	4/5	18°	32	1.3 (4.5)	1/7.5	52	CL-S1, CL-32S	Built-in	64 x 83.5	435	③	—	①	①	✓ 3	✓ 5
180mm f/2.8 ED	5/5	13°40'	32	1.8 (6)	1/7.5	72	CL-S4, CL-38	Built-in	78.5 x 130	800	②	—	②	—	✓ 2	✓ 5
200mm f/2 IF-ED ^{*2}	8/10	12°20'	22	2.5 (9)	1/9.5	Gelatin filter	CT-200	Built-in, HE-4	132 x 225.5	2,550	②	—	④	②	—	Not usable
300mm f/2.8 IF-ED ^{*2}	6/8	8°10'	22	3 (10)	1/8.3	39	CT-302	Built-in, HE-4	132 x 255	2,400	③	①	③	①	—	Not usable
400mm f/2.8 IF-ED ^{*2}	6/8	6°10'	22	4 (15)	1/8.3	52	CT-400	Built-in, HE-3	163 x 378.5	5,150	④	②	—	②	—	Not usable
400mm f/3.5 IF-ED ^{*2}	6/8	6°10'	22	4.5 (15)	1/9.8	122/39 ^{*4}	CL-61A	Built-in	134 x 296	2,800	—	①	③	①	—	Not usable
500mm f/4 P IF-ED ^{*2}	6/8	5°	22	5 (20)	1/9.1	39	CT-500	HK-17	138 x 384	3,000	—	①	—	①	—	Not usable
600mm f/5.6 IF-ED ^{*2}	6/7	4°10'	32	5 (20)	1/7.3	39	CT-603	Built-in, HE-4	132 x 387.5	2,800	—	①	—	①	—	Not usable
800mm f/5.6 IF-ED ^{*2}	6/8	3°	32	8 (30)	1/9.1	52	CT-800	Built-in, HE-3	163 x 546	5,450	—	②	—	②	—	Not usable
Reflex																
500mm f/8 ^{*2}	6/6	5°	—	1.5 (5)	1/2.5	82/39 ^{*4}	CL-39	HN-27	89 x 109	840	③	—	③	⑤	Not usable	✓ 5
1000mm f/11 ^{*2}	5/5	2°30'	—	8 (25)	1/7.1	39	CL-29	Built-in	119 x 233.5	1,900	③	⑤	—	⑤	—	Not usable
Zoom																
28-85mm f/3.5-4.5	11/15	74°-28°30'	22	0.8 (3) [0.23 (0.8)]	1/8.3 [1/3.4]	62	CL-S1, CL-33S	HK-16	67 x 89	510	①	—	①	—	✓ 0	✓ 0
35-70mm f/3.3-4.5	7/8	62°-34°20'	22	0.5 (2) [0.35 (1)]	1/6.7 [1/4.3]	52	CL-S1, CL-31S	HN-2	63 x 61	250	①	—	①	—	✓ 0	✓ 1
35-105mm f/3.5-4.5	12/16	62°-18°	22	1.4 (5) [0.27 (0.9)]	1/11.6 [1/4]	52	CL-S1, CL-33S	HK-11	64 x 86.5	510	①	—	①	—	✓ 0	✓ 0
35-200mm f/3.5-4.5	13/17	62°-12°20'	22	1.6 (5.5) [0.3 (1)]	1/7 [1/4]	62	CL-S3, CL-13A	HK-15	70 x 119	740	③	—	—	—	✓ 0	✓ 1
70-210mm f/4.5-5.6	8/11	34°20'-11°50'	32	1.5 (5)	1/6	52	CL-38	HR-1	64 x 104	375	①	—	①	—	✓ 2	✓ 3
Special Purpose																
PC 28mm f/3.5 ^{*1}	8/9	74°	22	0.3 (1)	1/6.7	72	CL-S2, CL-34A	HN-9	78 x 64.5	380	—	—	—	—	✓ ^{a,c} 0	✓ 0
PC Micro 85mm f/2.8D ^{*5}	5/6	28°30'	45	0.39 (1.3)	1/2	77	CL-75	HB-22	83.5 x 109.5	770	—	—	—	①	✓ ^{a,c} 0	✓ 0
Micro 55mm f/2.8 ^{*1}	5/6	43°	32	0.25 (0.9)	1/2	52	CL-S1, CL-31S, CL-32S, CL-33S ^{*6} , CL-15S ^{*6}	HN-3	63.5 x 62	290	①	—	①	—	✓ 1	✓ 3
Micro 105mm f/2.8 ^{*1}	9/10	23°20'	32	0.41 (1.34)	1/2	52	CL-S4, CL-32S, CL-33S, CL-38 ^{*7}	HS-14	66.5 x 83.5	515	①	—	①	—	✓ 3	✓ 5
Micro 200mm f/4 IF ^{*2}	6/9	12°20'	32	0.71 (2.34)	1/2	52	CL-S4, CL-36, CL-45	Built-in	66 x 172	800	—	①	③	①	✓ 2	✓ 5
Teleconverters																
TC-201	5/7	—	—	—	—	—	CL-S1, CL-30S	—	64.5 x 52	230	—	—	—	—	—	—
TC-301	5/5	—	—	—	—	—	CL-S1, CL-33S	—	64.5 x 115	325	—	—	—	—	—	—
TC-14A	5/5	—	—	—	—	—	CL-S1, CL-30S	—	65 x 25.5	145	—	—	—	—	—	—
TC-14B	5/5	—	—	—	—	—	CL-S1, CL-30S	—	65 x 34	165	—	—	—	—	—	—
Photographic Attachment	3/5	—	—	—	—	—	CL-S1	—	65.4 x 56	200	—	—	—	—	—	—

*1 Features Close-Range Correction (CRC) system.
 *2 Tripod mounting collar is provided.
 *3 Manual-type diaphragm with preset ring.
 *4 Front filter / rear filter.
 *5 The camera's exposure metering and flash control system do not work properly when shifting and/or tilting the lens, or when using an aperture other than the maximum aperture.
 Shifting and/or tilting the lens to a large degree can cause some vignetting.
 This lens cannot be used with the Nikon PRONEA S camera.
 *6 With a PK-13 ring.
 *7 With a PN-11 ring.

① Usable.
 ② When used at smaller aperture than f/11 with high shutter speeds, there is occasional uneven exposure.
 ③ Usable, but there is occasional vignetting.
 ④ There is occasional vignetting. And when used at smaller aperture than f/11 with high shutter speeds, there is occasional uneven exposure.
 ⑤ Usable if the rear screw-in filter is removed.
 — Not usable.

✓ Usable.
 *a Vignetting occurs.
 *b Slight vignetting occurs.
 *c Vignetting will occur only in certain situations.